

Standard Product Specifications Form

标准产品规格表

产品名称: Product Name:	21.5inch Touch Mirror		参考号: Ref. No.	RY90301A
产品型号: Model No.:	SNT-IPD-MTW21.5 SNT-IPD-MTA21.5		显示尺寸: Display Size:	21.5inch
产品设计主要模块 Major Customized Module	结构 Structure	触摸 Touch Panel	显示 Display	电脑 PC

SNT 产品设计全部采用组件模块化，以下内容基于产品 BOM 清单制作模块化信息，请认真阅读比对，以便于更好地了解产品规格

All SNT Products are using modularized assembly, following contents are with product modular design information based on product BOM list. Please read and check carefully, to better understanding the products specifications.

产品模块一： 结构

Module One: Structure:

正视产品尺寸: Dimension	520mm*316mm	直角边框 Straight Edge
边框厚度: Frame Thickness:	20mm	
背板厚度: Back Shell:	34.40mm	
边框颜色: Frame Color:	喷砂阳极银色 Silver/Anodization of sand blast	铝挤成型 Aluminum extrusion
边角处理: Edge Processing:	直拼，角马固定 Straight Fixing, Corner Connector	
背板颜色 Back shell Color	阳极黑色 Black	
背板结构: Back shell Structure:	四边折弯加固 Four side bending reinforcement.	
其他: Other Parts:		

产品模块二： 触摸


Module Two: Touch Panel

触摸屏尺寸: Touch Panel Size:	21.5inch 有效触摸区: Active Area: 476.06*267.79mm	参考附件图纸 Refer to drawings attached.
-----------------------------	---	---------------------------------------

玻璃规格: Glass Spec.:	4mm 镜面玻璃, 直角, 磨边 4mm Mirror Glass with side grinding, straight edge	非钢化 Non-tempered
镜面盖板玻璃尺寸: Mirror Touch Glass:	519*315mm	公差
电容触摸类型: Touch Sensor Type:	电容触摸 Capacitive Touch	ITO touch panel
触控芯片型号: Touch Controller IC:	ILITEK 2312	
反应速度: Touch Response:	<5ms	
触摸精准度 Touch Accuracy	±1mm	
扫描频率 Scan Frequency	120FPS	
工作电压 Working Voltage	USB2.0 5v	
触摸点数 Touch Points	10 点 10 Points	
其他: Other Parts:	TP/LCM 贴合方式: 全贴合 TP/LCM Lamination Type: Full Lamination (optical bonding)	

产品模块三: 显示

Module Three: Display

液晶屏型号: LCD Module:	AUO P215HVN01.0	
分辨率 Resolution:	FHD 1920*1080 (2K)	
亮度: Brightness:	300CD/m ² (Typ.)	
对比度: Contrast:	3000:1	
反应速度 Response Time	6.5ms	
可视角度 Viewing Angle	89/89/89/89 (Typ.)(CR≥10)	
寿命 Service Life	30,000 hours	

显示区域 Viewing Area	476.64(H)*268.11(V)	Unit: mm
输入电压 Input Voltage	100~240V, 50/60Hz	
插头类型 Plug Type	UL/VDE	需求出口欧美 Installation Destination: EU/US
其他: Other Parts:		

产品模块四：电脑可选

Module Four: PC Option A/B

A. Windows

电脑配置 Computer Configure	I5-6200U	
存储 Memory	4G RAM, 128G SSD	
网络 Internet	RJ45	
HDMI	*1	
USB	*4	
Mic	*1	
Line out	*1	
音响 Loudspeaker	5W*2	
其他: Other Parts:		

B. Android

CPU	MTK8173 4 Core Frequency 2.0GHz*2+1.6GHz*2	
存储 Memory	2G/16G	
安卓版本号 Android Version	Android 7.0	
网络 Internet	RJ45	
HDMI	*1	
USB	*2	
Blue Tooth	Support BT4.0	
其他: Other Parts:		

